Damp walls and heat loss

Moisture changes performance; there is no fixed percentage for every wall.

Build Supply | SulfRock | Intelligent Panel Systems | HomePod

1 What changes

Moisture can increase the thermal conductivity of porous materials and affect the thermal resistance of the wall.

2 Assess the whole wall

Heat loss depends on materials, thickness, moisture content, area, temperature difference and the whole building.

3 Locate the source

Investigate rain, plumbing, ground moisture, condensation and construction moisture.

4 Choose the repair

Repair the identified defect and consider how the construction dries. Do not cover over unresolved damp.

5 Review insulation

Check compatibility and moisture risk before adding insulation to an existing wall.

6 Measure where needed

Use suitable investigation or thermal assessment. A damp meter reading alone does not provide a whole-wall U-value.

Next step: identify the moisture source, repair it and reassess the wall performance.

REFERENCE GUIDANCE

GOV.UK: solid wall heat loss research
GOV.UK: resistance to moisture research

Use current product instructions and the approved project design. For regulations, confirm the UK nation, applicable edition and transitional arrangements.

Help us keep our information accurate.

If you notice an error, outdated information or something that needs clarification in this document, please let us know.
Report an Issue: Visit our website and select Report a Website or Document Issue.
homepodltd.com